



DATA SHEET FOR THREE PHASE MOTOR PART NUMBER 3RL0015

- **Type of protection** II 2G Ex db(eb) IIC T6...T4 Gb IP55 zone 1
 - (option II 2D Ex tb IIIC T 135°C Db IP 66)
- **Ambient temperature**
- -20 +60°C for **T4** , -20 +50°C for **T5**, -20 + 40°C for **T6**
- **Altitude above sea level** 1000m
- **Standard specification** IEC,ISO,EN
- **Certificate** : TUV IT13 ATEX 039X
- **Relative humidity** : 90%



ELECTRICAL DATA			GENERAL DATA	
Frequency (Hz) ± 2%	50	60	Frame size	80
Voltage ±5%	230/400	265/460	Type of construction	IMB 3/5/35/14/34
Power (Kw)	0,75	0,86	Weight (kg)	13,5
Motor speed (rpm)	1440	1656	Frame and Tbox material	Aluminium EN46100
Current (A) at V 230/400	3,46/2		Degree protection	IP 55 or IP66
Current (A) at V 265/460		3,46/2	Insulation	F class
Torque (N.m)	5,2	4,42	Duty	S1
Efficiency IE3	82,5		Cable entry	N.2 M 20x1,5
Power factor	0,7	0,7	Cooling type	IC411
Starting/rated motor current	4,9			
Starting /rated motor torque	1,9			
PTC temperature (°C)	120°C FOR T4 /90°C FOR T5 /70 °C FOR T6- MANDATORY FOR INVERTER DUTY			

MECHANICAL DATA	
Moment of inertia Kg m²	0,0022
Bearings	6204 2Z
Max axial load	254
Max radial load	580
Bearings maintenance	40.000 h
Noise level (dB)	78